



1138 Series

38 中控系列

38 Series Central Locking Caster

- 使用精密滾珠軸承。輪面有兩種選擇：PPR輪及全效輪。
另有提供活動，詳情請與我們聯絡。
- Pressed steel housing. Precision ball bearings in both swivel head and wheel.
Wheel tread with two options, TPR on PP core and Resolute rubber on PP core. Housing cover made of synthetic material. Swivel without central lock model is available, please consult factory.



Brake type	Wheel diameter (mm)	Width of Tread (mm)	Stem diameter (mm)	Stem length (mm)	Offset (mm)	Overall height (mm)	Load capacity (kg)	Swivel radius (mm)	Hole height (mm)	Hole diameter (mm)	Angle	Wheel Tread Material	ITEM NO.	
剎車型式	輪徑	輪寬	插桿直徑	插桿長度	偏心距	總高	載重	旋轉半徑	插桿六角孔中心高	插桿六角孔對邊	六角轉件角度	輪面材質	品號	
Swivel caster with total lock 二段	100	31	28	96	43.4	138.8	90	93.4	78.5	11.2	A	TPR on PP Core 超級人造膠	11380400268010	
											B		11380400268020	
	100	31	32	50	43.4	138.8	90	93.4	34	11.2	A		11380400268030	
											B		11380400268040	
	125	31	28	96	38	162.5	125	100.5	78.5	11.2	A		11380500268040	
											B		11380500268110	
	125	31	32	50	38	162.5	125	100.5	34	11.2	A		11380500268130	
											B		11380500268120	
	150	31	28	96	39	190	125	114	78.5	11.2	A		11380600268010	
											B		11380600268020	
	150	31	32	50	39	190	125	114	34	11.2	A		11380600268040	
											B		11380600268030	
	100	31	28	96	43.4	138.8	90	93.4	78.5	11.2	A		Resolute Rubber 全效輪	11380400458010
											B			11380400458020
	100	31	32	50	43.4	138.8	90	93.4	34	11.2	A			11380400458030
											B			11380400458040
	125	31	28	96	38	162.5	125	100.5	78.5	11.2	A			11380500458030
											B			11380500458050
	125	31	32	50	38	162.5	125	100.5	34	11.2	A			11380500458080
											B			11380500458090
	150	31	28	96	39	190	125	114	78.5	11.2	A			11380600458010
											B			11380600458020
	150	31	32	50	39	190	125	114	34	11.2	A			11380600458030
											B			11380600458040



Brake type	Wheel diameter (mm)	Width of Tread (mm)	Stem diameter (mm)	Stem length (mm)	Offset (mm)	Overall height (mm)	Load capacity (kg)	Swivel radius (mm)	Hole height (mm)	Hole diameter (mm)	Angle	Wheel Tread Material	ITEM NO.	
剎車型式	輪徑	輪寬	插桿直徑	插桿長度	偏心距	總高	載重	旋轉半徑	插桿六角孔中心高	插桿六角孔對邊	六角轉件角度	輪面材質	品號	
Swivel caster with total and directional lock 三段	100	31	28	96	43.4	138.8	90	93.4	78.5	11.2	A	TPR on PP Core 超級人造膠	11380400268050	
											B		11380400268060	
	100	31	32	50	43.4	138.8	90	93.4	34	11.2	A		11380400268070	
											B		11380400268080	
	125	31	28	96	38	162.5	125	100.5	78.5	11.2	A		11380500268030	
											B		11380500268010	
	125	31	32	50	38	162.5	125	100.5	34	11.2	A		11380500268140	
											B		11380500268020	
	150	31	28	96	39	190	125	114	78.5	11.2	A		11380600268050	
											B		11380600268060	
	150	31	32	50	39	190	125	114	34	11.2	A		11380600268080	
											B		11380600268070	
	Resolute Rubber 全效輪	100	31	28	96	43.4	138.8	90	93.4	78.5	11.2		A	11380400458050
													B	11380400458060
		100	31	32	50	43.4	138.8	90	93.4	34	11.2		A	11380400458080
													B	11380400458070
		125	31	28	96	38	162.5	125	100.5	78.5	11.2		A	11380500458040
													B	11380500458010
		125	31	32	50	38	162.5	125	100.5	34	11.2		A	11380500458100
													B	11380500458020
		150	31	28	96	39	190	125	114	78.5	11.2		A	11380600458050
													B	11380600458060
		150	31	32	50	39	190	125	114	34	11.2		A	11380600458080
													B	11380600458070

