



1110-YOYO Series

优优轮系列

YOYO Series-Light Duty Twin Wheel Caster (All Plastic)

- 大轮宽设计，行走稳定顺畅且静音、转动灵活、外形美观、两种煞车踏板（大vs小）供选择，满足客人多样化需求、转向易操控。
- Large caster width provide stability with soft PVC tread for quite operation. Customed exterior design provide great aesthetic value. Two types of brake pedals, big and small to choose from. Easy to maneuver.

载重 Load
45-100kg



特色区 Features



大踏板
Big pedal



小踏板
Small pedal



两种颜色供选择
Two different colors
to choose from

轮子选项 Wheel Options



PVC轮
PVC on PP Core

底板规格 TOP PLATE SIZE AND BOLT HOLE SPACING

底板尺寸 Top Plate Size	底板孔距 Bolt Hole Spacing	安装尼帽尺寸 Attaching Bolt Size
42X42mm	32X32mm	M4/M5
60X60mm	39X39mm / 46X46mm	M6
69X96mm	45X75mm (高级底板)	M8










插杆规格 CYLINDRICAL STEM SPECIFICATION

插杆直径x长度 Diameter x Length	孔位高度 Hole Height	孔尺寸 Bore Size
11X22mm	—	C型环(Grip Ring)
11X31.8mm	—	C型铜扣环(Grip Ring)
11X38mm	—	C型铜扣环(Grip Ring)
11X50mm	—	C型环(Grip Ring)

丝扣规格 THREADED STEM SPECIFICATION

M8X15mm (带法兰 With Flange)	M8X25mm	M10X15mm	M10X19mm
M10X25mm	M12X25mm	1/2-12UNCX25mm	1/2-13UNCX25mm
3/8-16UNCX25mm			



 轮径x轮宽 Diameter x Width	 规格 Specification	 载重 Load	 材质 Material	 型号 Item No.		 轴承 Bearing	 总高 Overall Height	 偏心距 Offset	 回旋半径 Swivel radius
				活动 Swivel	中刹 Center Brake				
轮面宽度 Width of Tread 65mm x 14.6mm (2.5" x 0.57") 脚轮宽度 Caster width 65mm x 59mm (2.5" x 2.3")	四角底板 Plate	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-25-113-2	1110-Y-25-113-4	—	81.5 mm	20 mm	活动 52.5mm 刹车(大踏板) 77mm 刹车(小踏板) 68.5mm Swivel 52.5mm Swivel W/Brake (Big pedal) 77mm Swivel W/Brake (Small pedal) 68.5mm
	丝扣 Threaded Stem	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-25-113-2	1110-Y-25-113-4				
	插杆 Cylindrical Stem	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-25-113-2(1)	1110-Y-25-113-4(1)		72 mm		
				1110-Y-25-113-2	1110-Y-25-113-4		79 mm		
轮面宽度 Width of Tread 73mm x 16.3mm (3" x 0.64") 脚轮宽度 Caster width 73mm x 63mm (3" x 2.48")	四角底板 Plate	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-03-113-2	1110-Y-03-113-4	—	90 mm	24.5 mm	活动 61mm 刹车(大踏板) 85mm 刹车(小踏板) 77mm Swivel 61mm Swivel W/Brake (Big pedal) 85mm Swivel W/Brake (Small pedal) 77mm
	丝扣 Threaded Stem	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-03-113-2	1110-Y-03-113-4				
	插杆 Cylindrical Stem	45kgs (110 lbs)	PVC轮 PVC on PP Core	1110-Y-03-113-2(1)	1110-Y-03-113-4(1)		80 mm		
				1110-Y-03-113-2	1110-Y-03-113-4		87 mm		
轮面宽度 Width of Tread 100mm x 18mm (4" x 0.71") 脚轮宽度 Caster width 100mm x 72mm (4" x 2.83")	四角底板 Plate	100kgs (220 lbs)	PVC轮 PVC on PP Core	1110-Y-04-113-2	1110-Y-04-113-4	精密轴承 Precision Ball Bearing	115 mm	32 mm	活动 82mm 刹车(大踏板) 105mm 刹车(小踏板) 99mm Swivel 82mm Swivel W/Brake (Big pedal) 105mm Swivel W/Brake (Small pedal) 99mm
	丝扣 Threaded Stem	100kgs (220 lbs)	PVC轮 PVC on PP Core	1110-Y-04-113-2	1110-Y-04-113-4				
	插杆 Cylindrical Stem	100kgs (220 lbs)	PVC轮 PVC on PP Core	1110-Y-04-113-2(1)	1110-Y-04-113-4(1)		105.5 mm		
				1110-Y-04-113-2	1110-Y-04-113-4		113 mm		

