



116S Series Heavy Duty AMR/AGV Spring-Loading Caster

Load
70 - 500 kg

- Caster fork is made of high tensile steel with harden raceway to provide long lasting service life and extreme high load capacity while maintaining low profile and overall height. It is suitable for application like AMR/AGV and robotic industry products. High quality spring design with excellent shock-absorbing capabilities keep machines carried by the caster stable while traveling across uneven surface.




Features

Wheel Options



Metal Thread Guard(optional)



ZQPU(Dual Wheels)



QPU



Ball Bearing



QPU(Dual Anti-Static Wheels)



King Kong Wheel

*Other Anti-Static Wheels Available, Please Contact The Factory

TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
2", 2.5"	51 x 65 mm (2" x 2-9/16")	36 x 51.5 mm (1-13/32" x 2-1/32")	6 mm (1/4")
	51 x 84 mm (2" x 3-5/16")	37 x 70 mm (1-15/32" x 2-3/4")	6 mm (1/4")
	60 x 60 mm (2-3/8" x 2-3/8")	42.5 x 42.5 mm (1-11/16" x 1-11/16")	6 mm (1/4")
	60 x 90 mm (2-3/8" x 3-17/32")	44.5 x 73 mm (1-3/14" x 2-7/8")	8 mm (5/16")
3", 4", 5", 6"	85 x 110 mm (3-11/32" x 4-11/23")	60 x 80~86 mm (2-3/8" x 3-5/32"~3-3/8")	8 mm (5/16")



 Diameter×Width	 Load	** Guarantee 2000 KM/ 1250 Miles	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
				Fixed	Swivel	Brake			
50mm x 20mm (41.5) (2" x 3/4")	70 kgs (154 lbs)	50 kgs (110 lbs)	ZQPU(Dual Wheels)	1165-02-101-1	1165-02-101-2	—	Ball Bearing	78mm (3-5/64")	Swivel 55 mm
	70 kgs (154 lbs)	50 kgs (110 lbs)	QPU(Dual Anti-Static Wheels)	1165-02-101-1	1165-02-101-2	—			
50mm x 40mm (2" x 1-9/16")	70 kgs (154 lbs)	50 kgs (110 lbs)	QPU	1165-02-53-1	1165-02-53-2	—			
50mm x 45mm (2" x 1-13/16")	70 kgs (154 lbs)	—	King Kong Wheel	1165-02-100-1	1165-02-100-2	—			
62.5mm x 20mm (41.5) (2-1/2" x 3/4")	250 kgs (551 lbs)	84 kgs (185 lbs)	ZQPU(Dual Wheels)	1165-25-101-1	1165-25-101-2	—	Ball Bearing	100mm (4")	Swivel 60 mm
	200 kgs (440 lbs)	67 kgs (147 lbs)	QPU(Dual Anti-Static Wheels)	1165-25-101-1	1165-25-101-2	—			
62.5mm x 45mm (2-1/2" x 1-13/16")	250 kgs (551 lbs)	—	King Kong Wheel	1165-25-100-1	1165-25-100-2	—			
	200 kgs (440 lbs)	67 kgs (147 lbs)	QPU	1165-25-80-1	1165-25-80-2	—			
75mm x 20mm (41.5) (3" x 3/4")	300 kgs (661 lbs)	100 kgs (220 lbs)	ZQPU(Dual Wheels)	1165-03-101-1	1165-03-101-2	—	Ball Bearing	116mm (4-9/16")	Swivel 65 mm
	250 kgs (551 lbs)	84 kgs (185 lbs)	QPU(Dual Anti-Static Wheels)	1165-03-101-1	1165-03-101-2	—			
75mm x 45mm (3" x 1-13/16")	300 kgs (661 lbs)	—	King Kong Wheel	1165-03-100-1	1165-03-100-2	—			
	250 kgs (551 lbs)	84 kgs (185 lbs)	QPU	1165-03-80-1	1165-03-80-2	—			
100mm x 22mm (41.5) (4" x 7/8")	400 kgs (881 lbs)	134 kgs (295 lbs)	ZQPU(Dual Wheels)	1165-04-101-1	1165-04-101-2	—	Ball Bearing	145mm (5-45/64")	Swivel 84 mm
	350 kgs (771 lbs)	117 kgs (257 lbs)	QPU(Dual Anti-Static Wheels)	1165-04-101-1	1165-04-101-2	—			
125mm x 24mm (41.5) (5" x 1")	500 kgs (1100 lbs)	167 kgs (368 lbs)	ZQPU(Dual Wheels)	1165-05-101-1	1165-05-101-2	—	Ball Bearing	175mm (7-1/8")	Swivel 102 mm
	450 kgs (992 lbs)	150 kgs (330 lbs)	QPU(Dual Anti-Static Wheels)	1165-05-101-1	1165-05-101-2	—			
150mm x 24mm (41.5) (6" x 1")	350 kgs (771 lbs)	117 kgs (257 lbs)	ZQPU(Dual Wheels)	1165-06-101-1	1165-06-101-2	—	Ball Bearing	200mm (8-1/8")	Swivel 130mm
	300 kgs (661 lbs)	100 kgs (220 lbs)	QPU(Dual Anti-Static Wheels)	1165-06-101-1	1165-06-101-2	—			

*The load is tested according to the ISO test standard

** Guarantee 2000 km life span on the selected AGV caster models under normal field application.
Dersheng reserves the right of the final interpretation on the caster test method and 2000 km guarantee.